

OKTRON-R

The OKTRON-R series are flat industrial control units with a mounting diameter of 16 mm - the round alternative to the square trend-setter OKTRON. The short stroke of 3 mm comes up with a very small mounting depth. As design and function of the OKTRON-R series are in close contact, many colour combinations can be realized by snap-on front bezels, which are also available in metal optics.

Degree of protection: IP65

Protection class: II



OKTRON-R

The OKTRON-R actuators fit the following contact blocks:

Standard contact blocks

Faston terminals 2.8 x 0.8 mm

Type series B...



Screw connections

Type series B...K (approvals on request)

Electronic contact units with snap action

PCB-mount terminals

Type series CTP...



Electronic contact units with snap action and up to two inverters

Faston terminals 2.8 x 0.8 mm

Type series CT...

PCB-mount terminals

Type series CZ... (approvals on request)



Technical Data:

acc. to VDE 0660 Ui~250V, Ith 6A

acc. to VDE 0630

IEC/EN 61058

250V AC 6 (4) A

Lamp voltage: 60V

Lamp socket: T5,5K/W2x4,6d

Lamp output: 1.2W max.



Rated voltage: 20mV...48V AC/DC (non-inductive)

max. current: 0.1A

min. current: 0.01mA

Lamp voltage: 60V

Lamp socket: T5,5K

Lamp output: 1.2W max.



Rated voltage: 20mV...48V AC/DC (non-inductive)

max. current: 0.1A

min. current: 0.01mA

Lamp voltage: 60V

Lamp socket: T5,5K

Lamp output: 1.2W max.



Mounting depth dimensions

