

OKTRON-JUWEL

Modern production machines, appliances with elaborate control panels – these are only a few examples for the usage of the OKTRON-JUWEL series, say everywhere, where the visual overall impression is a decisive factor. The control units feature first-class quality, high reliability and long-life cycle combined with an attractive design.

Degree of protection: IP65

Protection class: II



Internationaler
Designpreis
Baden-Württemberg
1998



Auszeichnung



OKTRON-JUWEL

The OKTRON-JUWEL actuators fit the following contact blocks:

Standard contact blocks
Faston terminals 2.8 x 0.8 mm
Type series B...



Technical Data:

acc. to VDE 0660 Ui~250V, Ith 6A
acc. to VDE 0630
IEC/EN 61058
250V AC 6 (4) A
Lamp voltage: 60V
Lamp socket: T5,5K/W2x4,6d
Lamp output: 1.2W max.



Electronic contact units
with snap action
PCB-mount terminals
Type series CTP...



Rated voltage: 20mV...48V AC/DC
(non-inductive)
max. current: 0.1A
min. current: 0.01mA
Lamp voltage: 60V
Lamp socket: T5,5K
Lamp output: 1.2W max.



Electronic contact units
with snap action and up to two
inverters
Faston terminals 2.8 x 0.8 mm
Type series CT...



Rated voltage: 20mV...48V AC/DC
(non-inductive)
max. current: 0.1A
min. current: 0.01mA
Lamp voltage: 60V
Lamp socket: T5,5K
Lamp output: 1.2W max.



PCB-mount terminals
Type series CZ... (approvals on request)

Mounting depth dimensions

