

# QUARTRON-JUWEL

The QUARTRON-JUWEL series combine attractive actuators with optimum exploitation of panel surface, smallest space requirement, toughness to all kinds of machines and utmost ease of assembly.

Degree of protection: IP65

Protection class: II



Extract of the QUARTRON-JUWEL product range



pushbuttons with  
illuminating and  
labelling option



key actuators



toggle heads



selector heads



emergency  
stops



# QUARTRON-JUWEL

The QUARTRON-JUWEL series fit the following contact units:

Standard contact blocks  
Faston terminals 2.8 x 0.8 mm  
Type series A...



## Technical Data:

acc.to VDE 0660 Ui~250V, Ith 6A  
acc.to VDE 0630  
IEC/EN 61058  
250V AC 6 (4) A  
Lamp voltage: 60V  
Lamp socket: T5,5K  
Lamp output: 1.2W max.



Electronic contact units  
with snap action

PCB-mount terminals  
Type series CTP...



Rated voltage: 20mV...48V AC/DC  
(non-inductive)  
max. current: 0.1A  
min. current: 0.01mA  
Lamp voltage: 60V  
Lamp socket: T5,5K  
Lamp output: 1.2W max.



Electronic contact units  
with snap action and up to two  
inverters

Faston terminals 2.8 x 0.8 mm  
Type series CT...

PCB-mount terminals  
Type series CZ... (approvals on request)



Rated voltage: 20mV...48V AC/DC  
(non-inductive)  
max. current: 0.1A  
min. current: 0.01mA  
Lamp voltage: 60V  
Lamp socket: T5,5K  
Lamp output: 1.2W max.



## Mounting depth dimensions

