

# RONTRON-Exclusive

We adapt your control units to their environment

The ultra-flat control units of the well-known, design-awarded series RONTRON-R-JUWEL and RONTRON-Q-JUWEL are presented in a new, sensational look: A high-quality surface in burl wood or carbon decor has been optimally combined with an elegant design. Thus, providing actuators that are predestined for the use in special environments making high individual demands on materials and design.

Even other decors can be realised according to customers' requirements.

The ring-shaped illumination of the pushbuttons will be perfectly colour-coordinated with the decor of the actuators and the control panel by choosing the appropriate LED.

Degree of protection: IP65

Protection class: II



# RONTRON-Exclusive

The RONTRON-Exclusive series fit the following contact blocks

## Standard Contact Blocks

Faston terminals 2.8 x 0.8 mm  
Type series B...



Screw connections  
Type series B...K (approvals on request)

## Electronic contact units with snap action

PCB-mount terminals  
Type series CTP...



## Electronic contact units with snap action and up to two inverters

Faston terminals 2.8 x 0.8 mm  
Type series CT...



PCB-mount terminals  
Type series CZ... (approvals on request)



## Technical Data:

acc. to VDE 0660 Ui~250V, Ith 6A  
acc. to VDE 0630  
IEC/EN 61058  
250V AC 6 (4) A  
Lamp voltage: 60V  
Lamp socket: T5,5K/W2x4,6d  
Lamp output: 1.2W max.



Rated voltage: 20mV...48V AC/DC (non-inductive)  
max. current: 0.1A  
min. current: 0.01mA  
Lamp: 60V  
Lamp socket: T5,5K  
Lamp output: 1.2W max.



Rated voltage: 20mV...48V AC/DC (non-inductive)  
max. current: 0.1A  
min. current: 0.01mA  
Lamp: 60V  
Lamp socket: T5,5K  
Lamp output: 1.2W max.



## Mounting depth dimensions

