













LED Indicator Selection Guide

Series	L30/31	L40/41	L50/51	L60/61	4000/3000	4400/7400
						
Mounting	Front snap in	Rear snap in	Front snap in	Rear snap in	Front snap in	Front with barrel fastener
Connection	Bipins, leads	Bipins, leads	Bipins, leads	Bipins, leads	Bipins, leads	Bipins, leads
Mounting hole	4mm	4.75mm	6.35mm	6.35mm	4.75mm	7.54mm
Housing	Black nylon UL94V-2	Black butyrate plastic, IP66 option	Black PP	Black butyrate plastic, IP66 option	Butyrate colored plastic, flat lens, custom printable, IP66	Aluminium body, clear or black, lens butyrate colored plastic, custom printable
LED	3mm, red, green, yellow, amber High efficiency, low current, bicolor	3mm, red, green, yellow, orange High efficiency, low current, bicolor, ultra bright, super ultra bright	5mm, red, green, yellow, orange High efficiency, low current, bicolor, ultra bright	5mm, red, green, yellow, orange High efficiency, bicolor, tricolor, ultra bright, super ultra bright, full color R/G/B	3mm, red, green, yellow, orange High efficiency, low current, bicolor, ultra bright, super ultra bright	5mm, red, green, yellow High efficiency, ultra bright, bicolor
Voltage	2 - 60 VDC, 120VAC	2 - 60 VDC, 120VAC	2 - 60 VDC, 120VAC	2 - 60 VDC, 120-240VAC	2 - 60 VDC, 120VAC	2 - 60 VDC, 120-240VAC

Series	100/600	CS/BS	CD	CR/BR	CC	CRM/BRM
						
Mounting	Front	Front screwable	Front screwable	Front screwable	Front screwable	Rear screwable
Connection	Bipins, leads	Bipins, leads	Bipins, leads	Bipins, leads	Bipins, leads	Bipins, leads
Mounting hole	7.93mm	M6	M6	M8	M8	M8
Housing	Butyrate colored plastic, flat lens, custom printable, IP66	Metal housing, inside reflector black finishing, IP66 option	Metal housing, outside reflector black finishing, IP66 option	Metal housing, inside reflector black finishing, IP66 option	Metal housing, outside reflector black finishing, IP66 option	Metal housing, outside reflector, black finishing, IP66 option
LED	5mm, red, green, yellow, orange High efficiency, bicolor, ultra bright, super ultra bright	3mm, red, green, yellow, blue, white High efficiency, low current, bicolor, ultra bright, nightvision	3mm, red, green, yellow, blue, white High efficiency, low current, bicolor, ultra bright, nightvision	5mm, red, green, yellow, orange, blue, white High efficiency, ultra bright, super ultra bright, bicolor, tricolor, full color R/G/B, nightvision, infrared	5mm, red, green, yellow, orange, blue, white High efficiency, ultra bright, super ultra bright, bicolor, tricolor, nightvision, infrared	5mm, red, green, yellow, orange, blue, white High efficiency, ultra bright, super ultra bright, bicolor, tricolor, nightvision, infrared
Voltage	2 - 60 VDC, 120-240VAC	2 - 60 VDC, 120VAC	2 - 60 VDC, 120VAC	2 - 60 VDC, 120-240VAC	2 - 60 VDC, 120-240VAC	2 - 60 VDC, 120-240VAC