

8800 Thinline Rocker Switches 10A 250Vac



- ▶ Ultra thin rocker switch
- ▶ Ratings up to 15A, 250Vac
- ▶ Single and twin gang
- ▶ Bezel sizes:
 - Single 21 x 9.5
 - Twin 21 x 15.5



10(6)A 250Vac T100
6(2)A 250Vac T100 5E4 (50,000 Operations)
Inrush 50A to EN60065:1998



UL CSA 15A 250Vac (Twin unit is 10A 250Vac)
UL CSA 125Vac 1/2hp
UL 100°C, file E45221, CSA file LR10990

In house test

10A 28Vdc






RoHS compliant

3mm contact gap.
Technical data on pages 4 & 5.

H 8800 V A - - -

TERMINAL FUNCTION ROCKER BODY PRINT, COLOUR, ETC

▶	TERMINAL	▶	FUNCTION	▶	ROCKER
H	 4.8 x 0.8		 Switches are ON when pressed over terminal 1	V	Curved
		8800	 ON - OFF Single pole		
			 Switches are ON when pressed over terminals 1 or 3		
T	 3.5 x 0.8 Solder	8800/8800	 ON - OFF Twin (Single pole)		



H8800VA ---
T8800VA ---



H8800VA ---
T8800VA ---




H8800V/H8800VA
T8800V/T8800VA



H8800V/H8800VA
T8800V/T8800VA


BODY

A Single pole



*Optional profile for orientation

A Single pole - Twin



*Optional profile for orientation

Panel thickness	Dim X
0.75-1.24	19.1/19.2
1.25-1.99	19.3/19.4
2.00-3.00	19.7/19.8

Cut-outs must be punched in the direction of insertion

OPTIONS

Finish

Matt finish only.

Colour


Call factory for custom colours.
A full range is available for large orders.

Legend printing


Select from the examples or call the factory
for custom legends.

Dimensions (mm)

8800VA (H terminals shown)



8800V/8800VA (H terminals shown)



Examples of printing



CL132



CL133

8500 Rocker Switches - Miniature

10A 250Vac Single & Double Pole



- ▶ Miniature rocker switch
- ▶ Ratings up to 15A, 250Vac
- ▶ High in-rush tolerance
- ▶ Single & double pole in same body size
- ▶ Illuminated & non-illuminated
- ▶ Matching indicators
- ▶ Industry standard panel cut-out
- ▶ Rotary and push button accessories



10(6)A 250Vac T125 (non lit types)
6(4)A 250Vac T125 5E4 (50,000 Operations) (non lit types)
10(6)A 250Vac T100 (lit types)



UL CSA 15A Non Ind 250Vac, 14A Ind 250Vac, 10A 277Vac
UL CSA 250Vac 1/2hp, 125Vac 1/4hp
UL 105°C, file E45221, CSA file LR10990

In house test

Inrush 85A to EN61058-1 & 10A 28Vdc



RoHS compliant

3mm contact gap.
Technical data on pages 4 & 5 (switches), 66 (indicators).

H 8550 V B ---
TERMINAL FUNCTION ROCKER BODY PRINT, COLOUR, VOLTAGE ETC

▶	TERMINAL	▶	FUNCTION	▶	ROCKER
H	 4.8 x 0.8	Approvals & ratings vary with function	 ON OFF Switches are ON when pressed over terminal 1	H	Slotted for custom adaptors
K	 2.6 x 0.8	8500	 ON - OFF Single pole (Uses terminals 1a & 2a)	R	Semi-rotary (not lit)
L	 2.8 x 0.8 Right angle version of K terminal available on 8500 only	8503	 ON (lit) - OFF Single pole	D	Paddle lever (not lit)
R	 4.8 x 0.8	8550	 ON - OFF Double pole	V	Curved (not lit)
T	 4.8 x 0.8 Solder	8553	 ON (lit) - OFF Double pole	V	Curved (lit)
		8580 Available with H terminals only	 Indicator	X	Two colour (not lit)
				A	Softline lens
				P	Push button operation (8500 only) See drawing opposite





H8500VB ---
T8500VB ---




H8550VB ---
T8550VB ---



H8550HB ---
T8550HB ---



H8550XB ---
T8550XB ---



H8550RB Semi-rotary
A splash proofing option



H8500PO ---



H8553VB ---
T8553VB ---




H8580AB ---

BODY


B

Standard body with terminal barrier

Panel cut-out




Bezel




BC

Body without terminal barrier

Panel cut-out



Bezel



Dimensions for snap-in fixing

Panel thickness	Dim X
0.75-1.25	19.1/19.2
1.25-2.00	19.3/19.4
2.00-3.00	19.7/19.8

Cut-outs must be punched in the direction of insertion

OPTIONS

Finish

Matt finish only.

Colour

Call factory for custom colours.
A full range is available for large orders.

Legend printing

Select from the examples or call the factory for custom legends.

Lamp voltage

Call factory for details of available voltages.


Protective cover L167

(designed to IP65)


Snaps on to bodies with V or X style rockers and A style lens, this reduces maximum acceptable panel thickness to 2.2mm.




DIMENSIONS (mm)



"B" body with barrier for H, T and K terminals



"BC" body w/o barrier primarily for L or R terminals
(can be used for all terminals)



'PO' Actuator and body - push button function (8500 only)

Examples of printing




CL076



CL080

10A 250Vac Single & Double Pole



In house test



UL CSA See ratings below
UL 65°C, file E45221, CSA file LR10990

Inrush 25A to EN61058-1 & 10A 28Vdc

RoHS compliant

3mm contact gap except where marked μ .
Technical data on pages 4 & 5 (switches), 66 (indicators).

TERMINAL	FUNCTION	ROCKER	BODY	PRINT, COLOUR, VOLTAGE ETC
----------	----------	--------	------	----------------------------

12



H8600VB ---
T8600VB ---



H8600VB ---
T8600VB ---



H8630FB ---
T8630FB ---



H8650VB ---
T8650VB ---



H8660VB ---
T8660VB ---




H8653VB ---
T8653VB ---


BODY

B Single pole

Panel cut-out



Bezel




Single Pole dimensions for snap-in fixing

Panel thickness	Dimension X
0.75-1.24	19.1/19.2
1.25-1.99	19.3/19.4
2.00-3.00	19.7/19.8


B (Double Pole) with terminal barrier

BC (Double Pole) w/o terminal barrier

Panel cut-out



Bezel



Double Pole dimensions for snap-in fixing

Panel thickness	Dimension X
0.75-1.24	19.1/19.2
1.25-1.99	19.3/19.4
2.00-3.00	19.7/19.8

Cut-outs must be punched in the direction of insertion

OPTIONS

Finish

Matt finish only.

Colour

Call factory for custom colours.
A full range is available for large orders.

Legend printing

Select from the examples or call the factory for custom legend.

Lamp voltage

Call factory for details of available voltages.

Blanking plate A8634FB

Dummy unit to fill unused panel holes.
Single pole size only.

Protective covers

L167 for SP

L180 for DP

(designed to IP65)

Snap on to bodies with V rocker or F lens, this reduces maximum acceptable panel thickness to 2.2mm.




Single Pole options

Most switches shown can have single pole switching in double pole bodies.


DIMENSIONS (mm)

Single pole



Terminals shown
are "H" 4.8 push on type

Double pole



Terminal spacing
10.2 between pole centres

For 8620 and 8670 dimensions see page 14

Examples of printing



CL076



CL080



CL141



CL142




CL059



CL058

8620 & 8670 Rocker Switches - 3 Positions 10A 250Vac



H8620VB --- H8670VB ---
 T8620VB --- T8670VB ---

- ▶ 3 position miniature rocker switch
- ▶ Ratings up to 15A, 250Vac
- ▶ Single & double pole
- ▶ Centre off switching
- ▶ Push on, solder and PCB terminals
- ▶ Matching indicators
- ▶ Bezel size
single: 21 x 15
double: 21 x 24



10(4)A 250Vac T90



UL CSA 15A 277Vac (Single pole)
 UL CSA 250Vac 1/2hp (Single pole)
 UL CSA 125Vac 1/4hp (Single pole)
 UL CSA 10A 277Vac (Double pole)
 UL CSA 125/250Vac 1/2hp (Double pole)
 UL CSA 277Vac 1/2hp (Single & Double pole)
 UL 90°C, file E45221, CSA file LR10990

In house test

10A 28Vdc



RoHS compliant

µ contact gap.
 Technical data on pages 4 & 5.


H 8620 V B ---

TERMINAL FUNCTION ROCKER BODY PRINT, COLOUR, ETC


▶ TERMINAL	▶ FUNCTION	▶ ROCKER	▶ BODY	▶ OPTIONS
H 4.8 x 0.8	 8620 ON - OFF - ON Single pole	V Curved 	B Single pole 12.9 Panel thickness 0.75-1.24 1.25-1.99 2.00-3.00 15.0 Dim X 19.1/19.2 19.3/19.4 19.7/19.8	Finish Matt finish only. Colour Call factory for custom colours. A full range is available for large orders. Legend printing Select from the examples or call factory for custom legends. Protective covers IP65 L167 for SP L180 for DP (designed to IP65) Snaps on to body, this reduces maximum acceptable panel thickness to 2.2mm.
T Ø2.15 Solder	 8670 ON - OFF - ON Double pole		B Double pole 21.9 Panel thickness 0.75-1.24 1.25-1.99 2.00-3.00 24.0 Dim X 19.1/19.2 19.3/19.4 19.7/19.8	
X 4.0 PCB 0.8sq Double pole switches with X terminals are supplied without terminal barriers			Cut-outs must be punched in the direction of insertion	

Dimensions (mm)


8620VB (H terminals shown)



8670VB (H terminals shown)



8670VB (X terminals shown)



Examples of printing



CL141



CL142

1250 Rocker Switches 10A 250Vac



10(6)A 250Vac T100
6A 400Vac T100
1A 30Vdc



UL CSA 10A 250Vac
UL CSA 16A 250Vac Resistive
UL CSA 125Vac 1/2hp
UL CSA 1A 30Vdc
UL 100°C, file E45221, CSA file LR10990

In house test

Inrush 75A to EN61058-1 & 10A 28Vdc



RoHS compliant

3mm contact gap
Technical data on pages 4 & 5

- ▶ Standard rocker switch
- ▶ Double pole in single pole body
- ▶ Snap in or sub panel mount
- ▶ Integral terminal barrier
- ▶ Push on or PCB terminals
- ▶ High inrush tolerance
- ▶ Bezel size:
29.5 x 15mm (snap in)
23.5 x 13mm (sub panel mount)














C1250AP - - -



C1250AN - - -


C 1250 A P - - -

TERMINAL FUNCTION ROCKER BODY PRINT, COLOUR, ETC


▶ TERMINAL	▶ FUNCTION	▶ ROCKER	▶ BODY	▶ OPTIONS
C  6.3 x 0.8	 On when pressed over terminal 1 1250  ON - OFF Double pole Poles are 9.0mm between centres.	A Curved  Shown in N body	N Panel cut-out Sub-panel  Facia  Bezel  Panel thickness 0.75-1.24 1.25-1.99 2.00-3.00 Dim X 26.1/26.2 26.3/26.4 26.7/26.8	Finish Matt finish only. Colour Call factory for custom colours. A full range is available for large orders. Legend printing Select from the examples or call factory for custom legends.
X  PCB 0.8sq (N body only)	 On when pressed over terminal 1 1250SP  ON - OFF Single pole	P Panel cut-out  Bezel  Panel thickness 0.75-3.00	Shown in P body	

Dimensions (mm)


1250AN (C terminals shown)



1250AN (X terminals shown)



1250AP (C terminals shown)



Examples of printing



CL085



CL086

6000 SP Splashproof Rocker Switches 16A 250Vac



- ▶ Single pole
- ▶ Ratings up to 20A, 277Vac
- ▶ High in-rush (ON-OFF types)
- ▶ Positive switch action
- ▶ Distinctive styling
- ▶ Illuminated & non-illuminated
- ▶ Matching indicator
- ▶ Bezel size: 31.5 x 14mm



European 16(4)A 250Vac T125, 10A 400Vac T125
UL CSA 20A 277Vac, 250Vac 11/2hp, 125Vac 1hp
UL 100°C, file E45221, CSA file LR10990

Inrush 150A* to EN61058-1 (ON - OFF only)
20A 28Vdc











* applies to non-momentary types




RoHS compliant

3mm contact gap with Positive Break switching.
Call factory for IP details.
Technical data on pages 4 & 5 (switches), 66 (indicators).

C 6003 A L ---
TERMINAL FUNCTION ROCKER BODY PRINT, COLOUR, VOLTAGE ETC

▶	TERMINAL	▶	FUNCTION	▶	ROCKER
	C  6.3 x 0.8		Approvals & ratings vary with function ON OFF Switches - ON when pressed over terminal 3 		A Softline Matt 
			6000 ON - OFF 		
			6001 ON - OFF (momentary ON) 		A Softline Matt 
			6002 ON - OFF (momentary OFF) 		Lit 
	H  4.8 x 0.8		6003 ON - OFF Lit 		P Lit window Matt 
			6008 ON - OFF Lit (Unswitched neutral) 		
			6009 ON - OFF (momentary ON) Lit (Unswitched neutral) 		A Lens Matt (6030 indicator only) 
	S  Screw & Clamp N/A for assemblies with 3 terminals		6010 ON - ON 		
			6011 ON - ON (momentary 1 side) 		
			6030 Indicator 		
			For twin switches and double pole circuits see pages 18 & 19		

For IP65 see “options” below



Integral Splashproofing

Current carrying parts are protected from moisture. Droplets which may enter the switch are channelled out through ports in the switch body.



C6000AL ---



C6000AL ---



C6010AL ---



C6003AL ---



C6003PL ---





C6030AL ---

BODY

L

Panel cut-out **

Bezel



OPTIONS

Finish Matt is standard.

Colour Call factory for custom colours. A full range is available for large orders.

Legend printing Select from the examples or call factory for custom legends.

Lamp voltage Call factory for details.

Protective cover (designed to IP65)


A snap on cover is available (add G after body code), this reduces maximum acceptable panel thickness to 2mm.



Panel sealing washer W46 is available, this reduces maximum acceptable panel thickness to 1.2mm. Covers are not suitable for momentary types.

For all options call the factory.

DIMENSIONS (mm)



Panel thickness

L 0.75 to 2.5mm

** For cut-out details on momentary switches call the factory

Cut-outs must be punched in the direction of insertion

Examples of printing



EN1224



EN1223

6050 DP Splashproof Switches - & Twins # 16A 250Vac



- ▶ Water thru design
- ▶ Ratings up to 20A, 277V ac
- ▶ High in-rush (ON-OFF types)
- ▶ Positive switch action
- ▶ Distinctive styling
- ▶ Illuminated & non-illuminated
- ▶ Double pole
- ▶ Bezel size: 31.5 x 25mm



European 16(4)A 250Vac T125, 10A 400Vac T125

UL CSA 20A 277Vac, 250Vac 1 1/2hp, 125Vac 1hp
UL 100°C, file E45221, CSA file LR10990

In house test

Inrush 150A* to EN61058-1
8(8)A 250Vac T125 5E4 on 6050 only
20A 28Vdc

* applies to non-momentary types


RoHS

RoHS compliant

3mm contact gap with Positive Break switching.
Call factory for IP details on Twin units.
Technical data on pages 4 & 5 (switches), 66 (indicators).
Patent app.

C 6053 A L ---
TERMINAL FUNCTION ROCKER BODY PRINT, COLOUR, VOLTAGE ETC

▶	TERMINAL	▶	FUNCTION	▶	ROCKER
	C 6.3 x 0.8		Approvals & ratings vary with function ON OFF Switches - ON when pressed over terminals 3 & 6 		A Softline Matt
	H 4.8 x 0.8		6050 ON - OFF	6060 ON - ON	
			6051 ON - OFF (momentary ON)	6061 ON - ON (momentary 1 side)	
			6052 ON - OFF (momentary OFF)	6062 2 Circuit ON - ON In house tests only	A Softline Matt
			6053 ON - OFF Lit	6066 ON - ON (Single pole) (isolated light)	A Softline Matt
			6054 ON - OFF (momentary ON) Lit	6067 ON - ON Lit	A Softline Matt Lit
			6055 ON - OFF (Single pole) (momentary ON) Lit	6068 ON - ON 1pole ON - OFF Lit 1pole	
			6056 ON - OFF (Single pole) Isolated light	6090 ON - OFF 1pole ON - OFF Lit 1pole	
			6057 ON - OFF Isolated light	6091 ON - OFF (momentary ON) Lit	
			6058 ON - OFF (Single pole) Lit	6092 ON - OFF 1 pole ON - ON 1 pole Lit	
	S Screw & Clamp N/A for assemblies with 3 terminals in either pole		6059 ON - OFF (Single pole) (momentary ON) Isolated light	Circuits are Double Pole unless described otherwise	P Lit Window Matt



Splashproof to IP44

Current carrying parts are protected from moisture. Droplets which may enter the switch are channelled out through ports in the switch body

For IP65 see options below



C6050AL ---



C6053AL ---



C6053PL ---



C6000A/C6000AL



C6003P/C6003PL




C6003P/C6030AL


BODY

L Double pole

Panel cut-out *




Bezel




L Twin units

Contact factory for information on splashproofing and IP ratings

Panel cut-out *



Bezel



Cut-outs must be punched in the direction of insertion

OPTIONS

Finish Matt is standard.


Colour Call factory for custom colours. A full range is available for large orders.

Legend printing Select from the examples or call factory for custom legends.

Lamp voltage Call factory for details.

Protective cover (designed to IP65 #)

The 6050 series is a water thru design. For a higher level of sealing, a snap on cover is available (add G after body code). This reduces maximum acceptable panel thickness to 2mm.



Panel sealing washer W42 is available, this reduces maximum acceptable panel thickness to 1.2mm. Covers are not suitable for momentary types.


IP Ratings Call the factory for details.

Terminal Link P1067 connects the poles of a double pole switch or twin unit.

Mounting orientation may affect IP rating.

For all options call the factory.

DIMENSIONS (mm)



Terminal spacing - Poles 10.5 between centres

Panel thickness

L 0.75 to 3.0mm

* For cut-out details on momentary switches call the factory

Examples of printing



EN1196



EN1197

1500 Standard & 1300 High Inrush Switches 150A to EN61058-1 and 16A 250Vac



- ▶ Standard rocker switch
- ▶ Non-illuminated
- ▶ 1300 high in-rush current
- ▶ Choice of switching circuits including 3 position
- ▶ Choice of bezel styles
- ▶ Choice of panel cut outs
- ▶ Matching indicator
- ▶ Single pole
- ▶ Splashproof option
- ▶ Bezel size 'A' style 30.2 x 14.0



In house test



In house test



1500 Series 16(4)A 250Vac T125

UL CSA 16A Non Ind 250Vac, (2 posn) 250Vac 1hp, 125Vac 1/2hp, (3 posn) 250Vac 1/2hp, 125Vac 1/4hp
UL 10A 14Vdc 'T' (1500 and 1510 only)
UL 85°C, file E45221, CSA file LR10990

20A 28Vdc

1300 series 16(6)A 250Vac T125 5E4 (50,000 Ops.) Ⓢ150A Inrush to EN61058-1

UL CSA 20A 250Vac 1hp, 125Vac 1/2hp
UL 85°C, file E45221, CSA file LR10990

20A 28Vdc

RoHS compliant

3mm contact gap except if marked μ .


Technical data on pages 4 & 5 (switches), 66 (indicators).

C 1300 A L ---

 TERMINAL FUNCTION ROCKER BODY PRINT, COLOUR, VOLTAGE ETC

TERMINAL	FUNCTION	ROCKER																														
C 6.3 x 0.8 H 4.8 x 0.8* K 2.8 x 0.8* T Solder U Right angle "T" solder terminal X PCB 0.8Sq* *N/A for 1300 series	Approvals & ratings vary with function ON OFF Switches - ON when pressed over terminal 1 <table> <tr> <th>Standard 1500</th><th>High Inrush 1300</th><th></th></tr> <tr> <td></td><td>Approvals apply to C & T terminals only</td><td>ON - OFF</td></tr> <tr> <td>1501 HP rating N/A</td><td></td><td>ON - OFF (momentary ON)</td></tr> <tr> <td>1502 HP rating N/A</td><td></td><td>ON - OFF (momentary OFF)</td></tr> <tr> <td>1510 μ HP rating N/A</td><td></td><td>ON - ON</td></tr> <tr> <td>1511 μ HP rating N/A</td><td></td><td>ON - ON (momentary 1 side)</td></tr> <tr> <td>1520 μ 125V & 250V 1/2 HP H terminal rated T100 only</td><td></td><td>ON - OFF - ON</td></tr> <tr> <td>1521 μ HP rating N/A H terminal rated T100 only</td><td></td><td>ON - OFF - ON (momentary 1 side)</td></tr> <tr> <td>1522 μ HP rating N/A H terminal rated T100 only</td><td></td><td>ON - OFF - ON (momentary 2 sides)</td></tr> <tr> <td>0430 X terminal N/A</td><td></td><td>Indicator Technical data on page 66</td></tr> </table>	Standard 1500	High Inrush 1300			Approvals apply to C & T terminals only	ON - OFF	1501 HP rating N/A		ON - OFF (momentary ON)	1502 HP rating N/A		ON - OFF (momentary OFF)	1510 μ HP rating N/A		ON - ON	1511 μ HP rating N/A		ON - ON (momentary 1 side)	1520 μ 125V & 250V 1/2 HP H terminal rated T100 only		ON - OFF - ON	1521 μ HP rating N/A H terminal rated T100 only		ON - OFF - ON (momentary 1 side)	1522 μ HP rating N/A H terminal rated T100 only		ON - OFF - ON (momentary 2 sides)	0430 X terminal N/A		Indicator Technical data on page 66	A Softline Matt
Standard 1500	High Inrush 1300																															
	Approvals apply to C & T terminals only	ON - OFF																														
1501 HP rating N/A		ON - OFF (momentary ON)																														
1502 HP rating N/A		ON - OFF (momentary OFF)																														
1510 μ HP rating N/A		ON - ON																														
1511 μ HP rating N/A		ON - ON (momentary 1 side)																														
1520 μ 125V & 250V 1/2 HP H terminal rated T100 only		ON - OFF - ON																														
1521 μ HP rating N/A H terminal rated T100 only		ON - OFF - ON (momentary 1 side)																														
1522 μ HP rating N/A H terminal rated T100 only		ON - OFF - ON (momentary 2 sides)																														
0430 X terminal N/A		Indicator Technical data on page 66																														

Enhanced Splashproofing



1500 W and B splashproof options

Feather edge seals and a close fitting collar protect current carrying parts from moisture.

B option has Hytrel collar/seals for enhanced protection.



C1500AR ---
T1500AR ---



C1500AL ---
T1500AL ---



C1500XL ---
T1500XL ---



C1510AL ---
T1510AL ---









C1520AL ---
T1520AL ---



C0430AL ---
T0430AL ---

BODY

Panel cut-out * Bezel
Cut-outs must be punched in the direction of insertion



OPTIONS

Finish Matt is standard.

Colour Call factory for custom colours. A full range is available for large orders.

Legend printing Select from the examples or call factory for custom legends.

Lamp voltage Call factory for details.

Blanking plates A0434 - - Dummy units to fill unused panel holes.


Protective cover (designed to IP65)
Snaps on to A, L, Q or T bodies (add G after body in cat no.), this reduces maximum acceptable panel thickness to 2mm.



Panel sealing washer W46 is available for the same body sizes, this reduces maximum acceptable panel thickness to 1.2mm. Covers are not suitable for momentary types.

For all options call the factory.

DIMENSIONS (mm)




Panel thickness

A, Q	0.75 to 3.3mm
L, B, T	0.75 to 2.5mm
R	0.75 to 3.0mm

* For cut-out details on momentary switches call the factory

1300 High inrush, positive break switching

The 1300 series mechanism ensures contact welds formed at switch-on, are positively separated by the plunger tube acting directly on the step in the moving contact.



Examples of printing



EN602A



EN730



EN822

5500 Lit Rocker Switches - Single Pole 16A 250Vac



- ▶ Standard rocker switch
- ▶ Illuminated
- ▶ Choice of switching circuits
- ▶ Choice of bezel styles
- ▶ Choice of panel cut outs
- ▶ Matching indicator
- ▶ Single pole
- ▶ Splashproof option
- ▶ Bezel size 'A' style 30.2 x 14.0



In house test



16(4)A 250Vac T85
10(3)A 250Vac T100, (12A 250Vac T125 for P rocker only)
UL CSA 15A 250Vac, CSA 16A Non Ind 250Vac
UL CSA 250Vac 1hp, 125Vac 1/2hp
UL 85°C, file E45221, CSA file LR10990
Inrush 24A to EN61058-1 & 20A 28Vdc

RoHS compliant

μ contact gap.
Technical data on pages 4 & 5 (switches), 66 (indicators).
For Twin units repeat the order details for both the left and right sides.

C 5503 A L ---
TERMINAL FUNCTION ROCKER BODY PRINT, COLOUR, VOLTAGE ETC

▶	TERMINAL	▶	FUNCTION	▶	ROCKER
C	 6.3 x 0.8	Approvals & ratings vary with function ON OFF Switches - ON when pressed over terminal 3			A Softline (Matt only) Lit
H	 4.8 x 0.8	5500 μ	ON - OFF		
		5503 μ preferred option	ON - OFF Lit Switched neutral		P Lit window (Matt only)
T	 Solder	5508 μ for special applications	ON - OFF Lit Unswitched neutral		



C5503AL ---



C5500AL ---



C5503PL ---



C5503A/C5430AL









C5503A/C5503AL



C5503P/C5503PL

BODY



Cut-outs must be punched in the direction of insertion

OPTIONS

Finish Matt is standard.

Colour Call factory for custom colours. A full range is available for large orders.

Legend printing Select from the examples or call factory for custom legends.

Lamp voltage Call factory for details.

Blanking plate A0434 -- (SP) A0494 -- (DP)
Dummy units to fill unused panel holes.


Protective cover (designed to IP65)
Snaps on to A, L, Q or T bodies (add G after body in cat no.), this reduces maximum acceptable panel thickness to 1.2mm.



Panel sealing washers W46 (Single Pole) and W42 (Double Pole) are available for these body types, this reduces maximum acceptable panel thickness to 2mm.

For all options call the factory.

DIMENSIONS (mm)




Terminal spacing - Poles 10.8 between centres (twin units)

Panel thickness

A,Q	0.75 to 3.3mm
L,B,T	0.75 to 2.5mm
R	0.75 to 3.0mm

Twin units

Two single switches or a switch and an indicator light can be assembled side by side in one double pole body. For 5500 range panel cut-out details (L, B and T) call factory.



For twin units the first set of order format details refer to the left hand unit, when looking at the front of the assembly. (This has terminal numbers 1, 2 & 3)

Examples of printing



EN3036



EN3064



EN706

1500 Twin Units Switches and Indicators 16A 250Vac



- ▶ Twin unit rocker switch
- ▶ Choice of switching circuits including 3 position
- ▶ Push-on, solder and PCB terminals
- ▶ Choice of bezel styles
- ▶ Choice panel cut outs
- ▶ Matching indicator
- ▶ Single pole
- ▶ Splashproof option
- ▶ Bezel size 'A' style 30.2 x 25.0



16(4)A 250Vac T125



UL CSA 16A 250Vac
UL CSA (2 posn) 250Vac 1hp, 125Vac 1/2hp, (3 posn) 250 Vac 1/2hp, 125Vac 1/4hp
UL 85°C, file E45221, CSA file LR10990

In house test

Inrush 36A to EN61058-1 & 20A 28Vdc

For versions with High Inrush or for 50,000 operations, see pages 20 and 26.



RoHS compliant


3mm contact gap except where marked μ .
Technical data on pages 4 & 5 (switches), 66 (indicators).
For twin units repeat the order details for both the left and right sides.

C 1500 A / C 1510 A L ---

TERMINAL FUNCTION ROCKER TERMINAL FUNCTION ROCKER BODY PRINT, COLOUR, ETC

▶	TERMINAL	▶	FUNCTION	▶	ROCKER
C	 6.3 x 0.8		Approvals & ratings vary with function ON OFF Switches - ON when pressed over terminal 1 or 4		A Softline (Matt)
H	 4.8 x 0.8	1500	ON - OFF		B Softline splashproof (Matt)
K	 2.8 x 0.8	1510 μ HP rating N/A	ON - ON		W Curved splashproof (Matt)
T	 Solder	1520 μ 125V & 250V 1/2 HP H terminal rated T100 only	ON - OFF - ON		X Two colour (Matt) (not momentary) ON - OFF only
X	 PCB 0.8Sq	0430 X terminal N/A	Indicator Technical data on page 66		A Softline lens (Matt) (Indicator)

Enhanced Splashproofing



1500 W and B splashproof options

Feather edge seals and a close fitting collar protect current carrying parts from moisture.

B option has Hytrel collar/seals for enhanced protection.



C1500A/C1500AL



C1500A/C0430AL



C1500X/C1500XL



C1520A/C1510AL




C1500A/C1520AL




C0430A/C0430AL

BODY


A Panel cut-outs




B




L




Q



R



T



Cut-outs must be punched in the direction of insertion

OPTIONS


Finish Matt is standard.

Colour Call factory for custom colours. A full range is available for large orders.

Legend printing Call factory for custom legends. State if a legend is to appear on the left or right hand unit (viewed from the front).

Lamp voltage Call factory for details.

DIMENSIONS (mm)



Call the factory for terminal spacing details

Panel thickness

A,Q	0.75 to 3.3mm
L,B,T	0.75 to 2.5mm
R	0.75 to 3.0mm

Twin unit terminal numbering

The first 6 digits of the catalogue number refer to the left hand unit when looking at the front. (This has terminal nos. 4, 5 & 6).

Examples of printing



EN602A



EN730

For all options call the factory.

1550 Standard & 1350 High Inrush Switches 150A to EN61058-1 and 16A 250Vac



- ▶ Standard rocker switch
- ▶ 1350/53 high inrush
- ▶ Choice of switching circuits including 3 position
- ▶ Push-on, solder and PCB terminals
- ▶ Choice of bezel styles
- ▶ Choice of panel cut outs
- ▶ Matching indicator
- ▶ Double pole
- ▶ Splashproof option
- ▶ Bezel size 'A' style 30.2 x 25.0



In house test



In house test



1550 Series 16(4)A 250Vac T125

UL CSA 16A 250Vac, (2 posn) 250Vac 1hp, 125Vac 1/2hp, (3 posn) 250 Vac 1/2hp, 125Vac 1/4hp.
UL 85°C, file E45221, CSA file LR10990.

20A 28Vdc.

1350 series 16(4)A 250Vac T85 1E4 (10,000 Ops.)
On request 16(6)A 250Vac T125 5E4 (50,000 Ops.)

150A Inrush to EN61058-1.

UL CSA 20A 250Vac 1hp, 125Vac 1/2hp.
UL 72Vdc 7A, 36Vdc 14A.

UL 85°C, file E45221, CSA file LR10990.

20A 28Vdc

RoHS compliant

3mm contact gap except if marked µ.
Technical data on pages 4 & 5 (switches), 66 (indicators).

C 1553 A L ---
TERMINAL FUNCTION ROCKER BODY PRINT, COLOUR, VOLTAGE ETC

▶ TERMINAL	▶ FUNCTION		▶ ROCKER
C 6.3 x 0.8	Approvals & ratings vary with function ON OFF Switches - ON when pressed over terminal 1 		A Softline Matt Lit (not momentary)
H 4.8 x 0.8*	Standard 1550	High Inrush 1350	B Splashproof Softline
	1551 HP rating N/A		V Curved Matt or gloss Gloss only Lit (not momentary)
	1552 HP rating N/A		W Splashproof Curved
K 2.8 x 0.8*	1553 Not W, X or B rocker	1353 Not W, X or B rocker	P Lit window Matt Lit (not momentary)
T Solder	1560 µ		X Two colour Matt
U Right angle T Solder (Not DP)	1561 µ HP rating N/A		F Flat lens Gloss (0480 only) (ON OFF only - not momentary) Top view
X PCB 0.8Sq*	1562 µ In house tests only		A Softline lens Matt (0480 only) as F but with raised profile
	1570 µ 125V & 250V 1/2 HP H terminal rated T100 only		R Round
	1571 µ HP rating N/A H terminal rated T100 only		
	1572 µ HP rating N/A H terminal rated T100 only		
	1484 µ In-house tested to 10(3)A 250Vac (B rocker only)		
	1487 µ In-house tested to 10(3)A 250Vac (B rocker only)		
	0480 X terminal N/A		



C1350AL ---



C1550XL ---



C1553PL ---



C1553RA ---
Shown with M614 bezel cover



C0480AL ---



Optional snap-in M441 barrier









C1553AA with additional
M616 guard
Cut-out 22.0/22.1 x 29.4/29.5
Guard accepts "A" body only



C0480RA ---

BODY

Panel cut-out * Bezel
Cut-outs must be punched in the direction of insertion



OPTIONS

Finish Matt is standard.

Colour Call factory for custom colours.
A full range is available for large orders.

Legend printing Select from the examples or
call factory for custom legends.

Lamp voltage Call factory for details.

Blanking plates A0494 Dummy units
to fill unused panel holes.


Protective cover (designed to IP65)
Snaps on to A, L, Q or T bodies (add G after body
in cat no), this reduces maximum acceptable
panel thickness to 1.2mm.



Panel sealing washer W42 is available for the
above body sizes, this reduces maximum
acceptable panel thickness to 2mm. Covers are
not suitable for momentary types.

For all options call the factory.

DIMENSIONS (mm)



Terminal spacing - Poles 10.2 between centres


Panel thickness

A,Q	0.75 to 3.3mm
L,B,T	0.75 to 2.5mm
R	0.75 to 3.0mm

* For cut-out details on
momentary switches call the
factory.

1350 High inrush, positive break switching

The 1350 series mechanism ensures
contact welds formed at switch-on,
are positively separated by the
plunger tube acting directly on the
step in the moving contact.



Examples of printing



EN602A



EN730



EN822

R13 Round Rocker Switches 6A 250Vac



- ▶ Miniature round rocker switch
- ▶ Ratings up to 10A, 250Vac
- ▶ Single & double pole
- ▶ Illuminated & non-illuminated, neon and LED
- ▶ Choice of actuators
- ▶ Matching indicator
- ▶ Bezel size: 23mm dia.



SP 6A 250Vac T85,
DP 10(4)A 250Vac T85



UL CSA SP 10A 125Vac & 6A 250Vac (For 16A call the factory)
UL CSA DP 8A 125/250Vac
UL 85°C, file E67774(S)
CSA file LR45128

RoHS

RoHS compliant

Single pole has μ contact gap.
Technical data on pages 4 & 5.

Standard products

Are supplied with the body and rocker colour, print & lamp voltage shown in the product illustration and description.

R13 112A AAA

TERMINAL FUNCTION ROCKER BODY PRINT, COLOUR, VOLTAGE ETC

PRODUCT DETAILS




SP ON - OFF μ

Cat no.
R13 112A AAA



SP ON - OFF μ

Cat no.
R13 112A AAB



SP ON - OFF μ
Lit 230V

Cat no.
R13 112B NAA



SP ON - OFF μ
Lit 230V

Cat no.
R13 112B NAB




DP ON - OFF

Cat no.
R13 244A AAA




SP ON - OFF μ
Lit 230V

Cat no.
R13 112B NAC



SP ON - ON μ

Cat no.
R13 112C AAA



SP ON - OFF - ON μ

Cat no.
R13 112D AAA



SP ON - OFF μ
(Momentary ON)

Cat no.
R13 208F AAA*




DP ON - OFF
Lit 230V

Cat no.
R13 244B NAA


DIMENSIONS (mm)

Panel cut-out




Snap fixing into panel thickness up to 3.0

Single pole



* R13 208F has 12.5mm deep body

Double pole



R13 Round Rocker Switches 6A 250Vac



6A 250Vac T85



UL CSA 10A 125Vac & 6A 250Vac (For 16A call the factory)
UL 85°C, file E67774(S)
CSA file LR45128



RoHS compliant

Single pole has μ contact gap.
Technical data on pages 4 & 5.

Special products

Are made to order and can be supplied with a range of body and rocker/lens colours, print & lamp voltage.
Call the factory for availability to your special requirements.

- ▶ Miniature round rocker switch
- ▶ Ratings up to 10A, 250V ac
- ▶ Single and double pole
- ▶ Illuminated and non-illuminated, neon and LED
- ▶ Choice of actuators
- ▶ Matching indicator
- ▶ Bezel size: 23mm dia.



R13 112A2 - -

TERMINAL FUNCTION ROCKER BODY PRINT, COLOUR, VOLTAGE ETC



PRODUCT DETAILS



SP ON - OFF μ
Bright colour ON signal

Cat no.



R13 112A2 - -



SP ON - OFF μ
Lit Window

Cat no.



R13 112B2 - -



SP ON - OFF μ
Paddle tip has red LED

Cat no.


R13 112LP - -




Indicator light

Cat no.

R9 92B - - -



PANEL CUT-OUT (mm)



Snap fixing into panel thickness up to 3.0



Protective cover L188

Snap on to bodies (not R13 211 or R13 112LP), this reduces maximum acceptable panel thickness to XXmm.

approvals - contact the factory